

2U Rackmount Chassis for Single Board Computer with 2 Drive bays, PICMG 1.0/1.3 backplane and support PS2 Single or Mini-redundant PSU

PS2 Single or Mini-redundant PSU


PICMG 1.0/1.3 Backplane

(2) 8cm ball-bearing fans

Latch front door with replaceable air filter

(2) 5.25" or (3) 3.5" Drive bays, or

(3) Mobile Racks (optional)



Introduction

The **RCK-202B** boasts a depth of only 450mm (17"), thus it provides an ideal solution for those applications where depth can make or break a project. Designed to support a PICMG1.0/ 1.3 Backplane and Full-Size SBC, the RCK-202B proves to be a perfect choice for any DVR or storage application. The RCK-202B can support up to three drive bays, (2) 5.25" or (3) 3.5" internal drives. Additional I/O expansion can be easily configured through the optional 2 or 4-PCI slots found on the PICMG backplane. Two 8cm ball bearing fans ensure excellent airflow when faced with a heat sensitive application. The RCK-202B provides a robust solution to any server application, while still remaining compact

Features


- EIA RS-310C 19" Rackmount Standard
- Heavy-duty Steel with Ni Plating
- (2) 5.25" or (3) 3.5" ext. drive bays, or
 (3) 3.5" Mobile racks (optional)
- Supports PICMG 1.0 and 1.3 backplane
- (2) 8cm ball-bearing fan with replaceable air filter
- Lockable front door with replaceable air filter
- Supports PS2 Single or Mini-redundant power supply
- Optional 18-inch ball-bearing slide rail



RCK-202B



Mechanical Drawing



Construction

Heavy-duty steel with Ni plating

Color

Black

Board Support

• Full-size Single Board Computer

Drive bay

- (2) 5.25" external drive bays, or
- (3) 3.5" internal drive bays, or
- (3) 3.5" Mobile racks (optional)

Expansion

 PICMG 1.0 / 1.3 backplane with PCI or PCIe slot expansion

Port

- (1) PS/2 connector on front panel
- (2) USB 2.0 connectors

Switch

Power On/Off, and Reset

Indicator

Power On/Off, and HDD activity LEDs

Cooling System

• (2) 8cm ball-bearing fan with replaceable air filter

Power Supply

- PS2 single PSU, up to 600W
- Mini-redundant PSU, up to 500W

Operation Temperature

● 0~55 °C

Dimension ($W \times D \times H$)

- 434 x 450 x 88 mm
- 17 x 17.7 x 3.5 inches

Weight

● GW: 10.2kg / 4.63lbs

Ordering Information

RCK-202B	2U Rackmount chassis for full-size SBC board with (2) 5.25" drive bays
RCK-202B-0604P- 400W	RCK-202B chassis with BP-0604P-2U b/p and 400W PS2 ATX Power supply
RCK-202B-0505P- 400W	RCK-202B chassis with BPE-0502-2U b/p and 400W PS2 ATX Power supply
RCK-202B-0502P- 400WR	RCK-202B chassis with BPE-0502-2U b/p and 400W Mini-redundant PSU
MR-K22C3	Mobile rack for (3) 3.5" SATA 2.0 HDD
MT-SR120	Optional 18-inch Ball-bearing slide rail

* Optional 600W PSU and 400W&500W Mini-redundant PSU are available for all above chassis configuration



16F-8 No.77, Sec. 1, Shin Tai Wu Rd, Hsi Chi Dist., New Taipei City 22101, Taiwan Tel: +886-2-2698-3280 Fax: +886-2-2698-3304

Sales: <u>sales @aicsys.com</u> Technical support: <u>support@aicsys.com</u> Website: <u>www.aicsys.com</u>