(2) 3.5" Drive bays


**Front Door Latch** 

**Drive bays** 



2U Rackmount Server Chassis for ATX M/B with 4 Drive bays, PCIe and PCI Riser card, supports 2U 500W Single or 2U 380W Redundant PSU

**2U Single or Redundant** 



### Introduction

The RCK-204M2 is a 2U Rackmount chassis that boasts a depth of only 450mm (17"), thus providing an ideal solution for those applications where the chassis depth can make or break a project. Equipped to handle ATX motherboards or Dual CPU server boards, the **RCK-204M2** proves to be a perfect choice for all ISP or Telecom applications. Exceeding the drive capacity of most 2U chassis, the RCK-204M2 can support up to four Drive bays - (1) 5.25" & (1) 3.5" ext. Drive bays, and (2) int. 3.5" Drive bays. A PCI riser card can be used with up to (3) PCI slots for additional peripherals. Two 8cm ball-bearing fans ensure excellent airflow when faced with a heat sensitive application. The RCK-204M2 provides a robust solution to any server application, while still remaining compact.

### **Features**


- EIA RS-310C 19" Rackmount Standard
- Heavy-duty Steel with Ni plating
- Supports ATX Motherboard
- Lockable Front Door for Maximum Access Security and Replaceable Air Filter
- (1) PS/2 connector on front panel
- (2) USB ports on front panel
- (2) 8cm Ball-bearing Fans
- Up to 2U 400W Single or 2U 380W Redundant Power supply
- Optional 18-inch Slide rail



# **RCK-204M2**



### **Mechanical Drawing**



### Construction

• Heavy-duty steel with Ni plating

#### Color

Black

### **Board support**

ATX motherboard

#### **Drive bays**

- (1) 5.25" & (1) 3.5" ext. Drive bays, and
- (2) 3.5" internal Drive bays

### **Expansion**

- PCI-303: (3) 32-bit PCI slots
- PCIE-303A: (1) 32-bit PCI, (1) PCIe x16
- and (1) PCIe x1 slots
- PCIE-303: (2) 32-bit PCI and
  (1) PCIe x16 slots

### **Power Supply**

- Up to 500W 2U Single, or
- Up to 380W 2U redundant PSU

### Cooling System

• (2) 80mm ball-bearing fans with replaceable air filter

### I/O Port

- (1) PS/2 connector
- (2) USB 2.0 port

### **Switch**

• Power On/Off and Reset switch

### **Indicator**

Power On/Off and HDD activity LEDs

### **Operating temperature**

● 0~55°C

### **Gross Weight**

• 9.4kg / 20.72lbs

### Dimension (W $\times$ D $\times$ H)

- 434 x 450 x 88mm
- 17.1 x 17.7 x 3.47 inches

## **Ordering Information**

RCK-204M2-PCI303-BLK RCK-204M2-PCIE303A-BLK RCK-RCK-204M2-PCIE303-BLK RCK-204M2-PCI303-400W-BLK RCK-204M2-PCI303-380WR-

**BLK** 

(2) PCI and (1) PCIe slots riser card 2U chassis for ATX motherboard w/ PCI303 riser card and 400W PSU 2U chassis for ATX motherboard w/

2U chassis for ATX motherboard

2U chassis for ATX motherboard

with PCI and PCIe slots riser card

2U chassis for ATX motherboard w/

with 3-slot PCI riser card

2U chassis for ATX motherboard w/ PCI303 riser card and 380W

redundant PSU

