

Introduction


The **WMC-302M** is designed to be an Industrial wall-mounted/ box system with one 5.25" external and one 3.5" internal Drive bays. The **WMC-302M** maintains a balanced internal temperature with two 80mm ball-bearing fans, front ventilation door with replaceable filter. **WMC-302M** offers robust solution for mounting your telecom, network, data center, imaging system, Server equipment in public area such as the CCTV surveillance recording or mobile broadcasting automation.


Features

- Compact industrial chassis
- Heavy-duty steel construction
- Support Mini-ITX motherboard
- (1) 5.25" ext. drive bay, and
 (1) 3.5" internal drive bay
- (2) Front USB 2.0 ports
- (1) Full-height expansion slot
- Front door with replaceable air filter
- Supports 1U single Power suply
- 235 x 320 x 132mm (WxDxH)











-320.30 [12.6198]-





Construction

- Heavy-duty steel, SECC 1.0t
- Color
- Black

Board support

• Mini-ITX motherboard

Drive bays

- (1) 5.25" external drive bay
- (1) 3.5" internal drive bay

Expansion

• (1) Full-height expansion slot

Power Supply

• Up to 520W single 1U Power supply

Cooling System

• (2) 60mm ball-bearing fans

I/O Port

• (2) USB 2.0 on front panel

Switch

• Power On/Off and Reset switch

Indicator

• Power On/Off and HDD activity LEDs

Operating temperature

- 0~55°C
- Dimension ($W \times D \times H$)
- 235 x 320 x 132mm
- 9.25x 12.6 x 5.19inches

Weight

• NW: 3.2kg / 7.1lbs

Ordering Information

WMC-302M-BLK	Mini chassis for Mini-ITX MB with 2
	drive bays, supports 1U PSU
WMC-302M-	Mini chassis for Mini-ITX MB with 2
300W-BLK	drive bays, and 300W PSU
WMC-302M-	Mini chassis for Mini-ITX MB with 2
460W-BLK	drive bays, and 460W PSU
WMC-302M-	Mini chassis for Mini-ITX MB with 2
520W-BLK	drive bays, and 520W PSU

