
RCK-413M



4U Rackmount Chassis for RAID storage with (3) 5.25" drive bays and (10) 3.5" hotswap mobile rack, (1) 80mm and (3) 120mm high speed ball- bearing fans and optional

80mm high speed ball-bearing fan

PS/2 or mini-redundant power supply

Three 120mm high-speed ball-bearing fans

(10) 3.5" Hot-swap mobile rack

(3) 5.25" Drive Bays



Introduction

RCK-413M is specifically designed as storage server. Within its long chassis it provides capacity of ten 3.5" Hotswap mobile-rack and three 5.25" applicable drive bays to contain large amount of data. Appropriate temperature within RCK-413M is sustained by one 80 mm and three 120mm high speed ball-bearing fans. Mini-redundant power supply is applicable to ensure minimum down time of the system. A lockable front cover is provided with RCK-413M to prevent unauthorized access to the unit. RCK-413M is very suitable for RAID application

Features


- Standard 4U 19" RAID storage chassis
- Heavy Duty Steel with Ni Plating
- ◆Ten 3.5" HDD (hotswap mobile rack applicable) and three 5.25" drive bays
- Supports mini-redundant or PS/2 power supply
- One 80mm and three 120mm high speed ball-bearing fans





RCK-413M



Mechanical Drawing









Construction

Heavy-Duty Steel with Ni Plating

Color

Black

Board Support

ATX motherboard

Drive Bays

• (10) 3.5" hot-swap mobile rack and (3) 5.25 external drive bays (Mobile rack applicable)

Expansion

• Up to (7) expansion slots

Power Supply

Mini-redundant or PS/2 power supply

Cooling System

• 80mm and (3) 120mm high speed ball-bearing fans

Ports

• (2) USB2.0 ports on front panel

Switches

On/Off Switch and Reset Switch

Indicators

- Power ON/OFF LED
- (2) Temperature Sensor LED
- Fan condition

Dimensions

- 427 (W) x 660 (D) x 176.8 (H) mm
- 16.8 (W) x 26 (D) x 7 (H) inches

Operating Temperature

● 0~55 °C

Gross Weight

• 22.3kg/49lbs

Ordering Information

RCK-413M 4U chassis for data storage

server with (10) drive bays

RCK-413M-400WR Same as above and with

400W mini redundant power

supply



16F-8 No.77, Sec. 1, Shin Tai Wu Rd, 221 Hsi Chi, Taipei Hsien, Taiwan T +886-2-2698-3280 F +886-2-2698-3304

Sales: sales@aicsys.com

Technical support: support@aicsys.com